## **Material Safety Data Sheet**

MSDS No 555

Product :

Perspex Cleaner

Issue Date January 21, 2015

Hazardous according to criteria of Worksafe Australia

#### COMPANY DETAILS

Adcoat Graphic Solutions Unit 3, 17 Stennett Street Ingleburn NSW 2565 Tel: 02 9605 3000

### **IDENTIFICATION**

Product Name	Perspex Cleaner		
Product Code	180326		
Proper Shipping Name	COMBUSTIBLE LIQUID		
Un Number	None Allocated		
DG Class	Non Allocated		
Packaging Group	Non Allocated		
Hazchem Code	Non Allocated		
Poisons Schedule	Not Scheduled		
Product Use	Graffiti Removal		
Physical Data			
Appearance, Odour	Yellow, clear liquid mild odour		
Melting Point	Not Applicable		
Boiling Point	100-174ºC		
/apour Pressure	Not Available		
Specific Gravity	0.94		
Flash Point	Not Applicable		
Flammability Limits	Not Applicable		
Solubility in Water	Soluble		
Other Properties			
/olatile Component	99.9%		
Autoignition Temperature	480ºC		
Evaporation Rate	Not Available		
Vapour Density	Not Available		
Ingredients			
Ingredients	Name	CAS	Proportion
	di sodium trioxoslicate	6834-92-0	<1%
	2-Butoxy Ethanol	111-76-2	60-70%
	Ethoxylated alcohols	68439-46-3	<1%
	coconut diethanolamide	8051-30-7	<1%
	ingredients determined not to be hazardous		to 100%
Continued on next page	2-Pyrrolidinone	872-50-4	<5% F

# **Material Safety Data Sheet**

Page 2 of 3

- - - - - -

MSDS No 555	Product :	Perspex Cleaner	Issue Date January 21, 2015
	Hazardous	according to criteria of Worksafe Australia	
Ingredients	<u>Name</u>	CAS	Proportion

## HEALTH HAZARD INFORMATION

Health Effects	
Acute - Swallowed Acute - Eye	Swallowing may cause irritation to mouth, throat and stomach possibly resulting in nausea and vomiting. May be an eye irritant.
Acute - Skin	Contact with skin may result in irritation. Repeated or prolonged exposure to the skin may cause dermatitis.
Acute - Inhaled Chronic	May cause irritation to the nose, throat and respiratory system with effects including dizziness and headache Chronic over exposure may result in skin irritation and defatting of the skin.

First Aid	
Swallowed	If swallowed, do not induce vomiting, rinse mouth thoroughly with water, give water to drink and seek urgent medical advice.
Eye Skin Inhaled	Flush eyes with plenty of water for 15 minutes and seek urgent medical advice. Remove contaminated clothing and wash affected area on skin thoroughly with soap and water. If irritation occurs, seek medical advice. Remove victim to fresh air. Remove contaminated clothing. Seek medical advice if adverse effects occur.
First Aid Facilities	Eye wash fountains and safety showers should be available for emergency use.
Advice to Doctor	

Advice to Doctor

**.** .

Treat symptomatically.

## Other Health Hazard Information

### PRECAUTIONS FOR USE

Exposure Limits	No exposure limits have been reported for this product. The following is a recommendation.
	2-pyrrolidone TWA = 103mg/m3 2-Butoxy Ethanol TWA = 25ppm
	Exposure Standard TWA is the Time Weighted Average airborne concentration over an eight hour working day for a five day working week over an entire working life.

## Personal Protection

Protective Equipment	<ul> <li>When exposure is likely, personal protection equipment in a combination appropriate to the degree and nature of exposure, should be selected from the following list :-</li> <li>(1) Eye protection</li> <li>(2) PVC gloves</li> <li>(3) PVC apron and sleeves, or full PVC apron</li> <li>(4) PVC or rubber boots</li> <li>(5) Respirator</li> </ul>
----------------------	--

# **Material Safety Data Sheet**

MSDS No 555

Product :

**Perspex Cleaner** 

Issue Date January 21, 2015

Hazardous

according to criteria of Worksafe Australia

#### Flammability

**Fire Hazards** 

Combustible liquid On burning will emit toxic fumes. Fire fighters to wear self contained breathing apparatus and suitable protective clothing. Extinguishing media - Water fog, foam, dry agent (carbon dioxide, dry chemical powder)

### SAFE HANDLING INFORMATION

#### Storage and Transport

Storage Precautions	Store secured in a dry well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store away from incompatible materials (strong oxidising agents)
Storage and Transport	Store in cool place out of direct sunlight. Store away from sources of heat or ignition. Ensure containers are in good condition and properly sealed.
Proper Shipping Name	COMBUSTIBLE LIQUID

#### Spills and Disposal

Spills & Disposal	Slippery when spilt. Shut off all possible sources of ignition. Increase ventilation. Use absorbent - sand or similar. Place used absorbent in suitable sealed & labelled containers for disposal. Wear appropriate personal protective equipment.
Disposal	Do not empty into drains or watercourses, inform local authorities if this occurs. Waste and empty containers must be disposed in accordance with local regulations.

#### **Fire/Explosion Hazard**

Fire/Explosion Hazard	COMBUSTIBLE LIQUID. May give off toxic fumes if engulfed in a large fire.
Hazardous Combustion Products	Combustion produces toxic fumes.
Extinguishing Media	Use extinguisher in accordance with primary source of fire. Extinguishing media - Water fog, foam, dry agent (carbon dioxide, dry chemical powder)
Hazchem Code	Non Allocated

## OTHER INFORMATION

#### Risk Statement

#### Safety Statement

Hazard Category S61 Avoid release to the environment. S62 If swallowed do not induce vomiting, seek medical advice immediately.

#### CONTACT POINT

Contact

Technical Services, Tel 02 96053000

Whilst every care has been taken in compiling these instructions, Adcoat Graphic Solutions, its employees, contractors and agents neither warrant or represent that the material published herein is accurate or free from errors or omissions. To the extent permissable by the law, ,Adcoat Graphic Solutions, its employees, contractors and agents shall not be liable or responsible for errors, omisions or misrepresentation made herein. The information given is based on our knowledge of health and safety data of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any purpose other than that for which it was intended. ,Adcoat Graphic Solutions responsibilty for products sold is subject to our standard terms and conditions sent to customers. No liability can be accepted with regard to the handling, processing or use of the product concerned which, in all cases, shall be in accordance with appropriate regulations and / or legislation.