



Proudly AUSTRALIAN owned

Liquid & Film Laminates
Penetrating Sealers
Advanced Water Based Coatings
Graffiti Removers & Cleaners
Full Coating Application Services

ADCOAT Graphic Solutions
Unit 3 / 17 Stennett Road
Ingleburn NSW 2565.
Ph: 02 9605 3000
Fax: 02 9605 3222
Tollfree: 1800 675 650

Technical Data Information

Product name : **Protekt-it – water based clear sacrificial anti-graffiti coating .**

Product Description :

ADCOAT **Protekt-it** is a single component water based coating system. This coating acts as a sacrificial barrier against all forms of graffiti, pollutants, moisture and even the penetration of felt pens, crayons and spray paints. It can be applied onto painted and unpainted surfaces including concrete, stone, timber, brick, concrete blocks, sandstone, limestone, Hebel blockwork, artworks, murals etc. Easy to apply.

Graffiti is easily removed using hot water without damage to the substrate.

- long term protection
- environmentally friendly
- applied to painted surfaces without harm
- applies as a milky solution and dries to a clear barely noticeable film
- removal process - hot water
- reduced absorption of water and pollution
- rapid drying time
- low odour
- stringent quality control procedures
- Australian owned and made

Technical Data :

Product: milky aqueous solution
specific gravity: 1.0
solids: 16% weight
dust free: 15 - 30 minutes*
odour: slight
coverage : 8 – 10 m² per litre per coat (depending upon relative humidity, air circulation, temperature and film thickness)

Surface Preparation :

Surface must be clean and sound, free from oils, surfactants, dust, chalk mildew and any other contaminants. If any of these are present then remove accordingly, either by scraping, sanding or power washing. Mildew must be removed with an appropriate solution.

Application :

Coating can be applied by low pressure airless spray, roller or brush.

A minimum of 1 - 2 coats are required, depending on the porosity of the substrate. ADCOAT **Protekt-it** should be applied to minimum of 60-100 microns DFT.

Do not apply below 10°C or above 85% relative humidity or when rain is imminent.

Ensure adequate air movement and sufficient ventilation.

Cleaning :

Wash up in hot water immediately after use.

COMMENTS :

Use only ADCOAT **Remove-it** if cold water cleaning process is used in preference to hot water and follow instructions carefully.

TECHNICAL HELP LINE.

If you require any further information or have any questions please call us on toll free 1800 675 650 and one of our experienced staff will be more than happy to assist.

The statements above are compiled from our field of production and according to the latest technological developments and application techniques. Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet. ADCOAT Graphic Solutions and associated group of companies shall not be responsible for any damage or injury resulting from abnormal use of the material, from any failure to adhere or observe the recommendations, or from any hazards inherent in the nature of the material. It is the users responsibility to evaluate the information contained herein and use this product safely and within the current laws and regulations.