



Proudly AUSTRALIAN owned.

Liquid & Film Laminates  
Penetrating Sealers  
Advanced Water Based Coatings  
Graffiti Removers & Cleaners  
Full Coating Application Services

**ADCOAT Graphic Solutions P/L**  
Unit 3 / 17 Stennett Road  
Ingleburn NSW 2565.  
Ph: 02 9605 3000  
Fax: 02 9605 3222

email : [sales@adcoatgraphicsolutions.com.au](mailto:sales@adcoatgraphicsolutions.com.au)

## Technical Data Information

**Product name: - Remove-it – organic, environmentally friendly graffiti remover**

### Product Description:

Remove-It is an ORGANIC, environmentally friendly, biodegradable, non caustic cleaner for the removal of most spray enamels, acrylics, permanent markers and lipstick off surfaces such as metal, stainless steel, ceramic tiles, porcelain, formica, timber, brick, concrete, natural stone and most surfaces treated with graffiti resistant coatings.

### **HOW TO USE ADCOAT REMOVE- IT.**

- **STEP 1** - Ensure that the surface and cleaning utensils (brushes, cloths etc) are completely dry and clean prior to removal.
- **STEP 2** - Commence removal work at the base and work upwards if on a vertical surface. Apply REMOVE-IT and work on small areas at a time. Agitate surface lightly with a stiff, natural bristle, brush and gradually work REMOVE-IT into surface. **DO NOT SCRUB!**
- **STEP 3** - Leave REMOVE-IT on for approximately 3-5 minutes. The ORGANIC compounds within REMOVE-IT will soften and do all the work.
- **STEP 4** - For stubborn or thick paint, apply additional REMOVE-IT and continue to work on this area with brushes.
- **STEP 5** - Wipe away any residue with dry, clean cloths continuing in a “spray and wipe” operation applying more REMOVE-IT until the surface is thoroughly clean.

**Note: DO NOT APPLY WATER** to the area being cleaned until all the graffiti and residue has been removed.

- **STEP 6** – Once clean ADCOAT REMOVE-IT **MUST BE NEUTRALISED** with water otherwise it will remain active and may damage your protective coating so wipe the cleaned surface thoroughly with a damp cloth or if possible, wash surface.

**Personal Protection:** all personal protection equipment as outlined in point (8) of the MSDS for this product is to be worn at all times when using this product.

- **The less time that the graffiti is allowed to cure on the surface, the easier it will be to remove.**
- **DO NOT at any time use scourers, steel wool or abrasives in conjunction with this product. Permanent and irreversible damage will be caused if this important note is ignored.**
- **ALWAYS test REMOVE-IT on a small area first to ensure that no adverse reaction occurs with the surface.**
- **Read the detailed instructions on data sheets and product labels prior to use. If you have any problems following these guidelines then do not hesitate to contact us for assistance.**

The statements above are compiled from our field of production and according to the latest technological developments and application techniques. Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet. ADCOAT Graphic Solutions and associated companies shall not be responsible for any damage or injury resulting from abnormal use of the material, from any failure to adhere or observe the recommendations, or from any hazards inherent in the nature of the material. It is the users responsibility to evaluate the information contained herein and use this product safely and within the current laws and regulations.